

TMP-2804 Series

Standard Specifications

Pump Main Unit

Turbo molecular pump		TMP-2804LM	TMP-2804LMC
Inlet flange		VG250 / ISO250B	
Outlet flange		KF40	
Cooling method		Water	
Ultimate pressure (after baking) (Note1)		10 ⁻⁷ Pa order	
Maximum allowable Argon gas flow rate		1250 mL/min (Note 1)	1900 mL/min
Maximum allowable inlet pressure (N ₂ continuous exhaust)		40 Pa	
Maximum allowable outlet pressure		270 Pa	
Pumping speed (Note 2)	N ₂	2800 L/s	
	Ar	2700 L/s	
	H ₂	2100 L/s	
	He	2800 L/s	
Compression ratio	N ₂	1 x 10 ⁹ or more	
	He	1 x 10 ⁵	
	H ₂	6 x 10 ³	
Rated speed		27600 rpm	
Start-up time		12 minutes or less	
Mounting position		In any desired direction	

Vibration level (by Shimadzu's method)		0.01 μ m or less (0-peak)
Recommended flow rate of purge gas		30 mL/min (Note 1)
Recommended pumping speed of backing pump in case of gas purge		1500 L/min or more
Environmental Temperatures		0 to 40 degrees C.
Admissible ambient magnetic field	Radial direction	3 mT
	Axial direction	15 mT
Water	Flow rate	2 to 4 L/min
	Pressure	0.2 to 0.5 MPa
	Temperature	5 to 25 degrees C.
Mass		84 kg

(Note 1)mL/min : volume flow rate at 0 degrees C., 1 atm. (compatible with SCCM.)(Note 2)Without a protective net for VG250 flange. Pumping speed for N₂ is 2550 L/s with a protective net.

Power Supply Unit

Power supply unit		EI-R04M
Battery		Not Necessary
Exchangeable compatibility		The control cable is interchangeable between any pump and power supply unit.
Speed variation		Speed is variable between 25 % and 100 % of the rated speed. (set as 0.1 %)
Communication	Contact	REMOTE (MR-34) Input : START / STOP / RESET / LOW SPEED Output : ROTATION / ACC. / BRAKE / NORMAL / REMOTE / ALARM / WARNING
	Serial	Front panel : RS-232C (D-sub 9 pin male, Screw lock size : M2.6)

		Rear panel : RS-485 (D-sub 9 pin female, Screw lock size : M2.6)
Environmental conditions	Temperature	Operation 0 to 45 degrees C. (No dew condensation)
	Relative humidity	40 to 80 %RH
Input electric power	Voltage	Single phase 200 to 240 VAC \pm 10 % (50/60 Hz \pm 2 Hz)
	Maximum power	1.5 kVA
Mass		8 kg